

10X Mini Speed Dome



Features

- 10X optical zoom, 10X digital zoom
- OSD menu with password protection, to display and program camera
- Hi-precision motor providing stable and precise performance
- P/T speed adjustable as per zoom times
- Manual-controlled scan area adjustable
- Auto/Manual start of heating device

Specification

Model	WS-HS10A
Zoom Module	Samsung 10X Zoom Module
Mounting Type	Surface, Wall, Pole
Signal Format	PAL/NTSC
Image Sensor	1/4" color CCD
Resolution	500TVL(Color), 570TVL(B/W)
Pan/Tilt Speed	Pan: 0.1~200°/sec, Tilt: 0.1~150°/sec
Illumination	0.02Lux
Day & Night	Yes
S/N Ratio	Not less than 50dB
AGC	Auto/Manual
BLC	Auto/Manual
Zoom	Optical: 10X, Digital: 10X
Lens	f=3.8-38mm F1.8
Pan/Tilt Range	Pan: 360° continuous; Tilt: 0 - 90°
Tracking Accuracy	0°~100°/sec
Preset Number	256
Auto Cruise	Auto swith from 0 to 30 preset positions sequentially
Pattern Scan	4 routes
Protocol	Pelco-D, Pelco-P etc.
Comm.Port	RS-485
Baud Rate	2,400bps, 4,800bps, 9,600bps, 19,200bps
Spectra Address	0~255
Operation Temperature	- 25°C ~ + 70°C
Power	DC12V, 15W

※※※ Product specification are subject to change without notice

www.winsafecctv.com www.winsafe-cctv.com