

# HD Video Conference Camera



## Features

- ◆1080i HD video format,suitable for HD TV transmission
- ◆Compatible with up to 14 formats,including 59.94Hz,50Hz and SD video etc
- ◆Video interfaces:Video,S-Video,VGA,**HD-SDI**
- ◆Equipped with remote controller, easy control and setting of cameras
- ◆Modern and compact design, quite mechanical movement...

## Specifications

Model	WS-HD11S
Zoom Module	SONY FCB-HD11
Signal Format	HD:1080i/59.94,1080i/50,720p/59.94,720p/50 SD:NTSC(Crop),NTSC(Squeeze),PAL(Crop),PAL(Squeeze)
Synchronization	Internal
Image Sensor	1/3 inch CMOS,2mega pixels
S/N Ratio	≤50dB
Shortest Focusing Distance	10mm(tele),80mm(wide)
Illumination	12Lux(50IRE)
Shutter	1/2~1/10000SEC
BLC	Auto /Manual
Zoom	Optical:10X,Digital:4X
Panning Range	Pan: 360°,Titl: - 30°~90°
Panning Speed	Pan: 0.1°~200°/sec,Titl: - 0.1°~150°/sec
Preset Position Number	64
Video output	<b>HD-SDI</b> Component(HD):D-sub 15pin Y:1Vp-p,75Ohm RCA(Standard definition) S-Video(Standard definition)
Comm. Port	RS 485
Baud Rate	1200bps,2400bps,4800bps,9600bps,19200bps
Protocol	VISCA,Pelco-D,Pelco-P
Spectra Address	0~255
Operating temperature	0°C ~ + 50°C
Storage temperature	- 20°C ~ + 70°C
Ambient Humidity	0~95%
Power	12VDC,10W
Dimensions	156 x 137 x140mm

※※※ Product specification are subject to change without notice

www.winsafecctv.com www.winsafe-cctv.com